

**ELECTRIC
STRIKE**



0563

1/2" RIM STRIKE



Low Energy
0.01A Auto-Sensing 12-24VDC



Strength
1500lbf Static
70 Dynamic ft-lb



Warranty
5 Year Limited Warranty



Door Frames
Surface Mount Design
Works With Most Material Types



Mode
Dual Mode Field-Selectable
Fail Safe & Fail Secure



PoE
PoE Friendly



Latch Monitor
Optional 0563LM Model

Designed for use with Pullman latch rim exit devices. Slim adjustable design ideal for tight-fitting installations.

0563

1/2" RIM STRIKE



Dimensions

1-3/4" x 9" x 1/2" (45mm x 230mm x 13mm)



Features

- Surface mounted – no frame cutting required
- Runs cool – does not heat up
- Includes two 1/8" spacers to accommodate all installations (5/8" & 3/4")
- Conventional keeper design (one moving part) – promotes even load distribution
- Lockdown holes for secure mount
- High-grade stainless steel ensures superior strength and creates a sleek aesthetic
- Non-handed – for use with right and left handed doors
- Compatible with most Pullman latch exit devices
- Accommodates exit devices with latch projections from 1/2"-3/4" (13mm-19mm)
- Horizontal adjustment ensures proper latch positioning to compensate for door misalignments - up to 1/4" (6.4mm)
- Auto-sensing 12-24VDC
- Plug-in wire connector
- Hex socket head cap screws for added support and tamper resistance
- Installation tool included (hex key)
- Patent pending

Options

- 0563LM – Latch monitor


Accessories

- 0563DDH – Double door housing (not compatible with 0563LM model)

Applications

- Commercial centers
- Industrial buildings
- Educational facilities
- Retail outlets
- Health care facilities
- Office complexes

Frame Type



Door Lock Type



Certifications & Testing

- UL 1034 Listed for 1500lbf of static strength



Model	Mode	Volts*	Current	Duty	Amps [†]
0563	Fail Safe/Secure	12-24	DC	Continuous	0.01
0563LM					

*Overheated or burnt PCBs caused by incorrect input voltage will not be covered under warranty. Maximum voltage must not exceed 28V.

[†]Steady state current. 0.17Amp peak.